

# COEX™ C3000 Thermal IP PTZ Camera Station

The COEX™ C3000 Thermal IP PTZ Camera Station has a unique compact and lightweight design developed specifically for hazardous-area applications. C3000 camera stations are designed for both toughness and durability as demanded for operation in the most adverse of environments, while allowing constant visual feedback in zero-light conditions.



COEX C3000 hazardous-area camera stations operate in the most extreme environments worldwide. Designed for toughness, durability, and certified to perform in ambient temperatures from -55°C to +70°C without compromise, they are ideal for oil and gas, marine, and industrial installations.

This premium-performance camera station delivers superb thermal imaging in all lighting conditions and across long distances.

Featuring the latest encoding technology (3<sup>rd</sup> generation IP encoder), the camera station is capable of triple-stream H.264 and H.265 encoding for simultaneous live view and recording.













Utilising the advanced radiometry feature, the camera station can provide real-time temperature data and differential temperature monitoring of critical devices and applications.

The C3000 Thermal IP PTZ Camera Station has cybersecurity measures built-in, including encrypted video streaming, HTTPS, and 802.1x protocols.

This camera station is compatible with a variety of VMS platforms through ONVIF Profile S and T compliance.

### Options

- Continuous rotation
- Advanced radiometry<sup>6</sup>

 ATEX	 IEC IECEx	 ONVIF S T
 -55°C/+70°C	 IP67/IP68	 316L STAINLESS STEEL
 H.264 H.265	 THERMAL SENSOR	 Triple Streaming
 60 FPS	 RADIOMETRICS	 CYBERSECURITY

# Specifications

CERTIFICATIONS / RATINGS <sup>4</sup>		[OPTIONS]
ATEX / IECEx / UKCA	ATEX II 2GD, Ex db IIB/IIC Gb; Ex tb IIIC Db; T4 / T5 / T6 EN60079-0, EN60079-1, EN60079-31, IEC60079-0, IEC60079-1, IEC60079-31	
ATEX / IECEx / UKCA Certified Temperature	-55°C to 40°C (T6), +50/60°C (T5), +70°C (T4)	
EMC	EN61000-6-2, EN 61000-6-4, Class A limits	
CE / UKCA	IEC62368-1, IEC60825-1	
DNV	TAA00001M2	
INMETRO	BRA 24.GE0010X	
ENVIRONMENTAL		
Operating Temperature	-45°C to +70°C / -49°F to +158°F	
Storage Temperature	-45°C to +80°C / -49°F to +176°F	
Ingress Protection	IP66 & IP68 (30m Submersion for 4 hrs) to IEC60529, Type 6 Enclosure	
Salt Mist	IEC60068-2-52 & IEC60945 Section 8.12	
Vibration	0.7 g to IEC60068-2-6 & IEC60945	
Wind Loading	Operational to 130 km/h, survival to 268 km/h	
Humidity	5% to 95%	
MECHANICAL		
Material	Electro-polished 316L stainless steel	
Window	Germanium window with DLC (Diamond-Like Carbon) coating and impact guard	
Pan Turning Circle	Ø 560 mm / 22.05"	
Tilt Turning Circle	Ø 360 mm / 14.17"	
Mounting Orientation	Upright or inverted	
Mounting Base	4 x M8 tapped holes, equispaced on a 4" (101.6 mm) P.C.D.	
Dimensions <sup>1</sup> (W x D x H)	375 x 310 x 352 mm / 14.76" x 12.21" x 13.86"	
Weight <sup>1</sup>	27 kg / 59.5 lbs	
Cable Gland Entries	2 x M20	
ELECTRICAL		
Power Requirements	24 V AC/DC (±10%) 50/60 Hz	
Power Consumption <sup>1</sup>	9 VA Quiescent 68 VA Operating 100 VA Max	
Auxiliary Inputs <sup>2</sup>	1 x contact closure input (5 V pull up) [additional inputs available on request]	
Relay Outputs <sup>2</sup>	1 x volt free switched output (24 V 0.75 A max) [up to 2 available on request]	
Audio <sup>2</sup>	[Line Input]	
CAMERA OPERATION		
	362° Rotation	Continuous Rotation
Pan Operation	0° to 42°/sec, mechanical limits, programmable soft-stops, preset positioning	0° to 42°/sec, programmable soft-stops, preset positioning
Tilt Operation	180° rotation, 0° to 21°/sec, mechanical limits, programmable soft stops, preset positioning	
Preset Functions	128 user programmable preset positions (pan, tilt digital zoom), preset accuracy <0.05°, absolute positioning	
ONVIF Control Features	PTZ control (continuous, relative and absolute) Preset store/recall, alarm inputs, and relay outputs	

THERMAL IMAGER	T306	T318	T618	T636
Image Sensor	Uncooled LWIR VOx microbolometer			
Pixel Pitch	12 µm			
Thermal Sensitivity	<50 mK at f/1.0			
Spectral Response	8 - 14 µm			
Refresh Rate	<9Hz [<60Hz] [25 Hz / 30 Hz]			
Pixel Resolution	320 x 256		640 x 512	
Fixed Focal Length	6.3 mm f/1.0	18 mm f/1.0	18 mm f/1.0	36 mm f/1.0
Angle of View	34.1° x 27.3°	12.7° x 9.7°	24.3° x 19.5°	12.2° x 9.8°
Radiometric Functionality Available	Yes	No	Yes	No
Features	8x digital zoom, auto/manual gain mode (AGC), auto/manual FFC(NUC), selectable colour palettes, second generation digital detail enhancement (DDE), image optimisation, active contrast enhancement (ACE), information based histogram equalisation (IBHEQ)			
Advanced Radiometry <sup>6</sup>	When used with Synergy, the advanced radiometry feature provides four regions of interest per preset position that can be individually monitored or compared against one another for temperature threshold changes.			
VIDEO ENCODING				
Compression Standards	H.264 (MPEG4 part 10/AVC) high, main, base profiles H.265 (MPEG-H part 2/HEVC), MJPEG			
Bitrate Mode	Constant Bitrate (CBR), Variable Bitrate (VBR)			
Encoding Capability	Up to 3 independently configurable encoded video streams			
Stream Bitrate <sup>3</sup>	100 kb/s to 25 Mb/s			
Image Resolution <sup>3</sup>	Native (640x512 or 320x256), D1 (720 x 576/480), VGA (640 x 480), QVGA (320 x 240)			
Image Rate <sup>3</sup>	Full, half, quarter, sixth			
GOP Structure	I-frame only, 5 to 240 frames			
Region of Interest (ROI)	Configurable per encoded video stream, ability to crop a selected area of the image source for encoding (variable resolution and aspect ratio)			
AUDIO ENCODING				
Compression Standards	ARM AACLC, ARM AACLC MPEG2, ARM AACHE, ARM AACHE V2			
Sample Rate	48 kHz, 44.1 kHz, 32 kHz, 16 kHz			
Stream Bitrate	12 to 384 kb/s (AACHE and AACHE V2 32 to 64 kb/s)			
NETWORK DEVICE				
Interface Options	Ethernet (100Base-T, 10-Base-T), Auto/full/half duplex, Auto/10/100, Configurable MTU Size			
Protocols	TCP/IP, UDP, ICMP, DHCP, DNS, HTTP, HTTPS, NTP, RTSP/RTP/RTCP, TSRTSP, RTMP, RTMPS, SRT, IGMP, SNMP, SYNS, SSL, TLS, 802.1x (EAP)			
Control Protocol	SYNS, ONVIF (Profile S, T compliant)			
Video Stream Delivery	RTSP/RTP (Unicast: UDP/TCP, Multicast UDP), TSRTSP, RTMP, RTMPS, SRT			
Network Discovery	SYNS, WS-Discovery (ONVIF)			
Device Security	Multiple users and 7 access levels protecting access to the web interface, ONVIF and RTSP services, HTTPS support, HTTP disable, 802.1x (EAP), video streaming disabled until change of default password, unicast stream disable			
Supported Internet Browsers <sup>5</sup>	Chrome/Firefox/Edge (No Active-X browser components required)			
System Maintenance	Field upgradeable firmware, diagnostic logs Hardware system supervisor providing temperature management, cold-start, auto-shutdown and watchdog control			

NOTE: \*1 Dependent on certification and equipment fitted. \*2 Dependent on cable tail option. \*3 Maximum permissible resolution, bitrate and framerate per additional stream will be reduced dependent on the configuration of the primary stream. \*4 Exact certification requirements must be specified at the time of order. \*5 Other browsers may be compatible but not tested. \*6 Advanced Radiometrics Service Pack 1. Advanced Radiometrics Service Pack 2 with added bonus features to follow.

## PART CODE STRUCTURE

C3 - A B C D - E - F G H J

(Example) C3 - 1 V [ ] T306 - [ ] - B 1 E X

**A - CAMERA HOUSING SIZE**  
1 Size 1 camera housing

**B - FIXED/PTZ**  
C PTZ - Continuous pan  
V PTZ - Non-continuous pan

**C - DAY/NIGHT CAMERA**  
N/A

**D - THERMAL IMAGING MODULE**  
T306 Medium resolution, 35° HFOV  
T318 Medium resolution, 13° HFOV  
T618 High resolution, 25° HFOV  
T636 High resolution, 12° HFOV

**E - WIPER**  
N/A

**J - SPECIAL**  
Standard build  
X Special build

**H - OUTPUT TRANSMISSION TYPE**  
E Ethernet Base-T

**G - BASE/MOUNTING TYPE**  
1 Standard PTZ mounting

**F - TECHNOLOGY SERIES**  
B 3rd Gen, IP encoder